

Certified
Quality VDE,
GS and CE

Small and Handy

The new electrode steam humidifiers CompactLine C01 and C02

There are two additions to the HygroMatik CompactLine: The HygroMatik C01 and HygroMatik C02 with steam output of 1 and 2 kg/h. As an ideal alternative for the smaller steam demand they ensure rapid steam production and precise control. Compact and space saving, they also fit in niches.

And like all CompactLine steam humidifiers they provide high HygroMatik quality components in long-lasting, stainless steel corrosion-resistant cabinets for easy wall mounting. Optional with fan unit for direct room humidification and remote control.

All signals set to green

- Hygienic humidification with clean steam
- Re-usable steam cylinder
- Easy changeable electrodes
- Reliable blow-down pump
- Intelligent microprocessor controls
- Certified
- Space saving and economical to your wallet



Type		C01	C02
Steam output	[kg/h]	1	2
Electrical supply		230V/1/N 50-60z	
Electrical power	[kW]	0.75	1.5
Current	[A]	3.3	6.5
Fuse	[A]	1x6	1x10
Control type		Basic, Comfort	
Control voltage		230 V	
Steam hose connection	[mm]	1x25	
Condensate hose connection	[mm]	1xDN9	
Empty weight	[kg]	8.5	10
Operational weight	[kg]	9.8	12.6
Dimensions	Height [mm]	370	350
	Width [mm]	347	384
	Depth [mm]	171	221
Water supply		1 to 10 bar, for connection 3/4"	

Subject to technical amendments without notice.

Contact your HygroMatik team for assistance:

Airtrend Ltd.-Gobrid. Ltd.
Kumanovska 14, 11000 Beograd
Tel. +381 11 383 68 86, 308 57 40
Faks +381 11 344 41 13
E-mail: gobrid@eunet.rs
www.airtend.rs

HYGROMATIK[®]
WE HUMIDIFY THE AIR